


HTG-B SERIES

The HTG-B series reflects **the Italian technological state-of-the-art and the manufacturers' solid engineering expertise.**

At **2,000, 3,000 and 6,000 litre** capacities, our flagship models are widely appreciated by industry experts and are virtually **maintenance free with close to zero servicing costs.**



HTG-B 2000

HTG-B 3000

HTG-B 6000

	HTG-B 2000	HTG-B 3000	HTG-B 6000
Dimensions [mm]	2850 x 1700 x 1600	3320 x 1950 x 2300	4300 x 2300 x 2680
Weight [kg]	2,000	2,200	2,900
Tank	2,150 litre hot-dip galvanized steel	3,100 litre hot-dip galvanized steel	6,100 litre hot-dip galvanized steel
Engine	Kohler (Extra EU) KDI 1903M/26 HP 40.23 Stage 3A	<ul style="list-style-type: none"> ▪ Kohler KDI-TCR 1903E5/26 (EU) 56 hp - 3 / Turbo Common Rail EU STAGE V - Diesel ▪ Kohler (Extra EU) KDI -TCQ1903U3/26 HP 56-3 Turbo Common Rail Stage 3A 	<ul style="list-style-type: none"> ▪ Kohler KDI-TCR 2504 (EU) 74 hp - 4 / Turbo Common Rail EU STAGE V - Diesel ▪ Kohler (Extra EU) KDI-TCk 2504 U3 HP 74-4 Turbo Common Rail Stage 3A
Pump	<ul style="list-style-type: none"> ▪ Self-priming positive displacement unit powered by a reversible hydraulic motor ▪ Flow rate 470 litres/min ▪ Head 10 bar ▪ Range approx. 25-30 m 	<ul style="list-style-type: none"> ▪ Self-priming positive displacement unit powered by a reversible hydraulic motor ▪ Flow rate 600 litres/min ▪ Head 14 bar ▪ Range approx. 35-40 m 	<ul style="list-style-type: none"> ▪ Self-priming positive displacement unit powered by a reversible hydraulic motor ▪ Flow rate 600 litres/min ▪ Head 14 bar ▪ Range approx. 35-40 m
Hydraulic mixing system	<ul style="list-style-type: none"> ▪ 4-blade mechanical mixer with 2 directions of rotation mounted on bearings flanged to the tank ▪ Driven by hydraulic motor ▪ Inner mix recycling 	<ul style="list-style-type: none"> ▪ 6-blade mechanical mixer with 2 directions of rotation mounted on bearings flanged to the tank ▪ Driven by hydraulic motor ▪ Inner mix recycling 	<ul style="list-style-type: none"> ▪ 9-blade mechanical mixer with 2 directions of rotation mounted on bearings flanged to the tank ▪ Driven by hydraulic motor ▪ Inner mix recycling
Hydraulic oil system	<ul style="list-style-type: none"> ▪ 2 pumps flanged to the internal combustion engine ▪ 2 reversible motors ▪ 80 litre oil reservoir with level indicator and thermometer ▪ Automatic heat exchanger 	<ul style="list-style-type: none"> ▪ 2 pumps flanged to the internal combustion engine ▪ 2 reversible motors for mixer and pump ▪ 95 litre oil reservoir with level indicator and thermometer ▪ Automatic heat exchanger 	<ul style="list-style-type: none"> ▪ 2 pumps flanged to the internal combustion engine ▪ 2 reversible motors for mixer and pump ▪ 115 litre oil reservoir with level indicator and thermometer ▪ Automatic heat exchanger
Piping	2" 1/2	3"	3"